

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 February 2005 (03.02.2005)

PCT

(10) International Publication Number
WO 2005/009541 A1

(51) International Patent Classification⁷: **A62B 1/06**

(21) International Application Number:
PCT/KR2004/001785

(22) International Filing Date: 19 July 2004 (19.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10-2003-0051573 25 July 2003 (25.07.2003) KR

(71) Applicant and

(72) Inventor: CHUN, Jung-Myung [KR/KR]; 12-2, Young-
woon-ri, Sanyang-up, Tongyong city, Kyongsannam-do
650-943 (KR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): KIM, Myoung-Oh

[KR/KR]; Room. 502, Samsung Apt 2dong, 290-2, Man-
duk-dong, Puk-gu, Pusan 616-826 (KR). CHUN, Jae-Ry-
oong [KR/KR]; Room.B-9, 1398, Chongnyang-dong,
Tongyong city, Kyongsannam-do 650-030 (KR).


(74) Agent: CHUN, Hoy-Nam; Room No. 206, Hanju Bldg
647, Yeoksam-dong, Kangnam-gu, Seoul 135-080 (KR).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: PERSONAL DESCENT APPARATUS



(57) Abstract: A personal descent apparatus for evacuating occu-
pants from a high elevation of tall building under emergency. The
personal descent apparatus comprises a pair of supporting plates
connected to each other front and rear with a predetermined gap,
braking rods rotatably fixed to the pair of supporting plates in the
predetermined gap between the pair of supporting plates, the brak-
ing rods form a passage which is formed by two guide grooves each
of which is tapered and formed at arc ends facing to each other, so
that a rope is inserted to the passage, and weight receiving means
connected to both ends of the braking rods for receiving a load,
wherein the braking rods are rotated by the load.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

- *with international search report*